

PRODUCT DATA SHEET

IDEMITSU 4T 20W-40 MA



Description

Idemitsu 4T 20W-40 MA is a premium Semi Synthetic 4-Stroke two wheeler engine oil developed in Japan. It offers following benefits –

1. Superior protection of engine's critical parts
2. Improved reliability even at higher operating temperature
3. Cleaner engine for longer period of time

Typical Characteristics

1. Premium Semi-Synthetic formulation for superior protection
2. Higher oxidation stability that reduces oil thickening & sludge formation
3. Better engine cleanliness

Typical Specifications

ITEM	ASTM METHOD	IDEMITSU 4T 20W-40 MA (Typical Value)
Viscosity Grade		SAE 20W40
Color	D-1500	L2.5
Density 15 °C g/cm ³	D-4052	0.8805
Flash Point (COC) °C	D-92	238
Viscosity, cSt	@ 40 °C	119.6
	@ 100 °C	13.99
Viscosity Index	D-2270	116
Acid Number (mgKOH/g)	D-664	2.02
TBN HClO ₄ (mgKOH/g)	D-2896	7.40
Foaming @ 93.5°C (ml)	D-892	10-0

The information provided is to our best knowledge, true & accurate, subjected to change without notification due to continual product research and development. All recommendations or suggestions are without guarantee since the conditions of use are beyond our control. The manufacturers do not accept liability for any loss or damage, however arising, which results directly from the use of such information, nor do we offer any warranty of immunity against patent infringement.