

# PRODUCT DATA SHEET

## IDEMITSU SUPER TRACTOR THF



### Description

Idemitsu Super Tractor THF is a specially designed lubricant for transmission & hydraulic system of agricultural machineries and construction equipment fitted with oil immersed brakes. Engineered & formulated in Japan, Idemitsu Super Tractor THF comes with special additives to ensure effective braking with reduced brake noise & damage.

### Application

Recommended to use in tractors and other agri & construction machineries fitted with oil immersed brakes.

### Characteristics

- Unique extreme pressure & anti wear properties ensure long life of transmission & hydraulic components
  - Excellent protection from corrosion & rust
  - Better de-foaming characteristics
  - Improved thermal & oxidation stability

### Typical Characteristics

CHEMICAL AND PHYSICAL PROPERTIES		TEST METHOD	TYPICAL DATA
Viscosity Grade			NA
Color		ASTM D-1500	L2.5
Density 15 °C g/cm <sup>3</sup>		ASTM D-4052	0.8773
Flash Point (COC) °C		ASTM D-92	234
Viscosity, cSt	@ 40 °C	ASTM D-445	56.92
	@ 100 °C	ASTM D-445	8.085
Viscosity Index		ASTM D-2270	110
Acid Number (mgKOH/g)		ASTM D-664	3.34
TBN HClO <sub>4</sub> (mgKOH/g)		ASTM D-2896	8.56
Foaming @ 93.5°C (ml)		ASTM D-892	0-0

The information provided is to our best knowledge, true & accurate, subjected to change without notification due to continual product research and development. All recommendations or suggestions are without guarantee since the conditions of use are beyond our control. The manufacturers do not accept liability for any loss or damage, however arising, which results directly from the use of such information, nor do we offer any warranty of immunity against patent infringement.

**Idemitsu Lube India Pvt. Ltd.**

603, 6th Floor, Eros Corporate Tower, Nehru Place, New Delhi - 110019, Tel: +91-11-30823600  
E-mail: [consumercareindia@idemitsu.com](mailto:consumercareindia@idemitsu.com) | Website: <https://india.idemitsu.com>