

PRODUCT DATA SHEET

IDEMITSU AGRI-MAX 15W-40 CH-4



Description

Idemitsu Agri-Max 15W-40 CH-4 is a high quality multi-grade diesel engine oil designed especially for tractors & other agri-machineries equipped with turbo & non-turbo diesel engines. Special formulation ensures excellent protection of engine's critical parts from mechanical wear, provide outstanding cleanliness and assure a steady & reliable performance.

Application

Recommended to use in tractors & other agri-machineries equipped with turbo & non-turbo diesel Engines.

Characteristics

- Excellent protection of engine parts from wear & tear even during high RPM & load.
 - Outstanding detergent-dispersant properties for cleaner & healthier engine.
 - Very good viscosity stability for steady performance.

Typical Characteristics

CHEMICAL AND PHYSICAL PROPERTIES		TEST METHOD	TYPICAL DATA
Viscosity Grade			SAE 15W-40
Color		ASTM D-1500	L2.5
Density 15 °C g/cm³		ASTM D-4052	0.8750
Flash Point (COC) °C		ASTM D-92	242
Viscosity, cSt	@ 40 °C	ASTM D-445	107.8
	@ 100 °C	ASTM D-445	14.48
Viscosity Index		ASTM D-2270	138
Acid Number (mgKOH/g)		ASTM D-664	2.0
TBN HCLO₄ (mgKOH/g)		ASTM D-2896	11.7
Foaming @ 93.5°C (ml)		ASTM D-892	0-0

The information provided is to our best knowledge, true & accurate, subjected to change without notification due to continual product research and development. All recommendations or suggestions are without guarantee since the conditions of use are beyond our control. The manufacturers do not accept liability for any loss or damage, however arising, which results directly from the use of such information, nor do we offer any warranty of immunity against patent infringement.