

PRODUCT DATA SHEET

IDEMITSU IFD5 5W-30 Idemitsu Four wheel Dual



DESCRIPTION

IDEMITSU IFD5 engine oils are for gasoline and diesel engines which offer low friction and high fuel economy. They are intended for use at extended oil drain intervals in passenger cars and light-duty gasoline and diesel engine.

APPLICATION

Only use in Gasoline and Diesel Engine vehicles where 5W-30 engine oil is recommended.

TYPICAL CHARACTERISTICS

Items		ASTM METHOD	IFD5 5W-30 API SN/ACEA C2 (Typical Value)
Viscosity grade			SAE 5W-30
Color		D-1500	L2.5
Density 15°C g/cm ³		D-4052	0.8530
Flash Point (COC)°C		D-92	228
Viscosity, cSt	@40°C	D-445	63.05
	@ 100°C	D-445	10.76
Viscosity Index		D-2270	162
Acid Number (mgKOH/g)		D-664	2.17
TBN HClO ₄ (mgKOH/g)		D-2896	8.11
Foaming @ 93.5°C (ml)		D-892	40-0

The information provided is to our best knowledge, true & accurate, subjected to change without notification due to continual product research and development. All recommendations or suggestions are without guarantee since the conditions of use are beyond our control. The manufacturers do not accept liability for any loss or damage, however arising, which results directly from the use of such information, nor do we offer any warranty of immunity against patent infringement.