

PRODUCT DATA SHEET
**IDEMITSU IFD7 5W-40 SN/A3 B4
Idemitsu Four wheel Dual**

DESCRIPTION

IDEMITSU IFD7 is formulated for 4-wheel gasoline and diesel engine vehicles which offer high durability, long-life performance, anti-wear engine protection and high piston cleanliness.

APPLICATION

Only use in Gasoline and Diesel Engine Vehicles where 5W-40 engine oil is recommended.

TYPICAL CHARACTERISTICS

| Items | ASTM METHOD | IFD7 5W-40 SN/A3B4 (Typical Value) |
|---------------------------------|-------------|---------------------------------------|
| Viscosity grade | | SAE 5W-40 |
| Color | D-1500 | L3.0 |
| Density 15°C g/cm ³ | D-4052 | 0.8520 |
| Flash Point (COC)°C | D-92 | 224 |
| Viscosity, cSt | @40°C | 79.29 |
| | @ 100°C | 13.26 |
| Viscosity Index | D-2270 | 170 |
| Acid Number (mgKOH/g) | D-664 | 1.95 |
| TBN HClO ₄ (mgKOH/g) | D-2896 | 10.10 |
| Foaming @ 93.5°C (ml) | D-892 | 0-0 |

The information provided is to our best knowledge, true & accurate, subjected to change without notification due to continual product research and development. All recommendations or suggestions are without guarantee since the conditions of use are beyond our control. The manufacturers do not accept liability for any loss or damage, however arising, which results directly from the use of such information, nor do we offer any warranty of immunity against patent infringement.