

**IDEMITSU IFG7 0W-16 SP/GF 6B  
Idemitsu Four Wheel Gasoline**

**DESCRIPTION**

Our top of the line IDEMITSU IFG7 engine oil is nano-tailored to optimally complement high-precision engines. Through Septet Guard technology, it offers super protection in 7 ways to realize ultimate driving performance.

**APPLICATION**

Only use in Gasoline Engine vehicles where 0W-16 engine oil is recommended.

**TYPICAL CHARACTERISTICS**

Items	ASTM METHOD	IFG7 0W-16 SP/GF-6B (Typical Value)
Viscosity grade		SAE 0W-16
Color	D-1500	L2.5
Density 15°C g/cm <sup>3</sup>	D-4052	0.8490
Flash Point (COC)°C	D-92	222
Viscosity, cSt	@40°C	28.40
	@ 100°C	6.677
Viscosity Index	D-2270	205
Acid Number (mgKOH/g)	D-664	2.44
TBN HClO <sub>4</sub> (mgKOH/g)	D-2896	8.51
Foaming @ 93.5°C (ml)	D-892	10-0

The information provided is to our best knowledge, true & accurate, subjected to change without notification due to continual product research and development. All recommendations or suggestions are without guarantee since the conditions of use are beyond our control. The manufacturers do not accept liability for any loss or damage, however arising, which results directly from the use of such information, nor do we offer any warranty of immunity against patent infringement.