

PRODUCT DATA SHEET

IDEMITSU 5W-40 SN A3/B4 FULLY SYNTHETIC Power & Protection



Description

Idemitsu SN A3/B4 5W-40 is a Full-Synthetic engine oil specially designed for those who look for performance, efficiency and thrill without worrying much about the engine protection even during extreme driving conditions. Engineered in Japan, it promises engine efficiency and protection based on Idemitsu's century long experience in lubricant making.

Application

Recommended for all high performance modern cars where SAE 5W-40 is recommended by OEMs

Characteristics

- Fully Synthetic engine oil
- Excellent start-up performance in low temperature and great durability at high temperature
- Minimize friction to optimize engine's performance
- Provides more stringent sludge control for piston and other engine parts, consequently keeping engine clean for longer engine life
- Provides superb protection against wear and corrosion
- Meets the requirements of API SN, ACEA A3/B4

Typical Characteristics

ITEM	ASTM METHOD	IDEMITSU 5W-30 SN/GF-5 SEMI SYNTHETIC (Typical Value)
Viscosity Grade		SAE 5W-40
Color	D-1500	L3.0
Density 15 °C g/cm ³	D-4052	0.8531
Flash Point (COC) °C	D-92	238
Viscosity, cSt	@ 40 °C	83.21
	@ 100 °C	13.87
Viscosity Index	D-2270	172
Acid Number (mgKOH/g)	D-664	2.25
TBN HClO ₄ (mgKOH/g)	D-2896	10
Foaming @ 93.5°C (ml)	D-892	0-0

The information provided is to our best knowledge, true & accurate, subjected to change without notification due to continual product research and development. All recommendations or suggestions are without guarantee since the conditions of use are beyond our control. The manufacturers do not accept liability for any loss or damage, however arising, which results directly from the use of such information, nor do we offer any warranty of immunity against patent infringement.