

PRODUCT DATA SHEET

IDEMITSU 4T 10W-30 MA SEMI SYNTHETIC Power & Protection



Description

Idemitsu 10W-30 MA is a Semi Synthetic engine oil especially formulated for new generation 4-stroke motorcycles, offers superior engine efficiency & smooth power delivery. It reduces friction and provides superb fuel economy. A smart partner for your daily worry-free rides.

Application

Recommended for all modern 4-stroke motorcycles where SAE 10W-30 viscosity is recommended

Characteristics

- High fluidity and excellent cold start at low temperature
- Excellent high temperature protection
- Specially formulated additives reduces friction and provides superb fuel economy

Typical Characteristics

ITEM	ASTM METHOD	IDEMITSU 4T 10W-30 MA SEMI SYNTHETIC (Typical Value)
Viscosity Grade		SAE 10W30
Color	D-1500	L2.5
Density 15 °C g/cm ³	D-4052	0.8634
Flash Point (COC) °C	D-92	240
Viscosity, cSt	@ 40 °C	64.82
	@ 100 °C	10.35
Viscosity Index	D-2270	138
Acid Number (mgKOH/g)	D-664	2.01
TBN HClO ₄ (mgKOH/g)	D-2896	7.47
Foaming @ 93.5°C (ml)	D-892	20-0

The information provided is to our best knowledge, true & accurate, subjected to change without notification due to continual product research and development. All recommendations or suggestions are without guarantee since the conditions of use are beyond our control. The manufacturers do not accept liability for any loss or damage, however arising, which results directly from the use of such information, nor do we offer any warranty of immunity against patent infringement.