

PRODUCT DATA SHEET

IDEMITSU 4T 10W-30 MB SEMI SYNTHETIC Power & Protection



Description

Idemitsu 10W-30 MB is a Semi Synthetic engine oil formulated exclusively for modern 4-stroke automatic scooters. Engineered with Friction Modifier (FM) additives, it ensures effortless power delivery and smooth riding experience along with improved fuel economy. A smart partner for your daily worry-free ride.

Application

Recommended for all modern 4-stroke automatic scooters where SAE 10W-30 viscosity is recommended

Characteristics

- Specially added friction modifiers for better engine efficiency & fuel economy
- High fluidity and excellent cold start at low temperature
- Smooth riding experience

Typical Characteristics

ITEM	ASTM METHOD	IDEMITSU 4T 10W-30 MB SEMI SYNTHETIC (Typical Value)
Viscosity Grade		SAE 10W30
Color	D-1500	L2.5
Density 15 °C g/cm ³	D-4052	0.8645
Flash Point (COC) °C	D-92	252
Viscosity, cSt	@ 40 oC	69.17
	@ 100 °C	10.41
Viscosity Index	D-2270	137
Acid Number (mgKOH/g)	D-664	2.05
TBN HClO ₄ (mgKOH/g)	D-2896	7.80
Foaming @ 93.5°C (ml)	D-892	20-0

The information provided is to our best knowledge, true & accurate, subjected to change without notification due to continual product research and development. All recommendations or suggestions are without guarantee since the conditions of use are beyond our control. The manufacturers do not accept liability for any loss or damage, however arising, which results directly from the use of such information, nor do we offer any warranty of immunity against patent infringement.