

PRODUCT DATA SHEET

IDEMITSU DIESEL 15W-40 CI4



Description

Idemitsu Diesel 15W-40 CI4 comes with revolutionary NGENMAX technology which ensures engine protection, enhances performance and improves engine cleanliness. Engineered with carefully chosen Additives & highly refined based oil, Idemitsu Diesel 15W-40 is sure to give more confidence through quality & performance reliability.

Application

Recommended to use in Commercial Vehicles such as Trucks, Busses & Tractors where SAE 15W-40 is recommended by vehicle manufacturers.

Characteristics

- Creates uniquely formulated strong film structure around the engine metal parts thus reducing the chances of metal to metal contacts even during high pressure & high operating temperature.
- Enables to pull out maximum torque effect by reducing internal drag & friction resulted into better engine efficiency & performance.
- Ensures excellent Detergent-Dispersant performance which reduces chances of soot agglomeration by having the soot particles dispersed in the engine oil thus keeping engine clean for longer duration.

Typical Characteristics

ITEM	ASTM METHOD	IDEMITSU DIESEL 15W-40 CI4 (Typical Value)
Viscosity Grade	-	SAE 15W-40
Color	D-1500	L2.5
Density 15 °C g/cm ³	D-4052	0.8750
Flash Point (COC) °C	D-92	242
Viscosity, cSt	@ 40 °C	107.8
	@ 100 °C	14.48
Viscosity Index	D-2270	138
Acid Number (mgKOH/g)	D-664	2.00
TBN HClO ₄ (mgKOH/g)	D-2896	11.7
Foaming @ 93.5 °C (ml)	D-892	0

The information provided is to our best knowledge, true & accurate, subjected to change without notification due to continual product research and development. All recommendations or suggestions are without guarantee since the conditions of use are beyond our control. The manufacturers do not accept liability for any loss or damage, however arising, which results directly from the use of such information, nor do we offer any warranty of immunity against patent infringement.