

PRODUCT DATA SHEET

DAPHNE SUPER COAT TW High Performance Anti Rust Oil

Description

Daphne Super Coat TW is a low viscosity rust preventive oil specially formulated with highly refined light mineral oil and various types of anti-rust additives for protection of highly finished metal surfaces such as bolts and nuts. It readily adheres to metal surfaces and forms a uniform continuous protection film on exposed metal surfaces for long-term indoor storage.

Application

Recommended as a rust preventive oil for protection of:

- Steel plate, pipe, rod, wire
- Bolts & nuts, gear, spring

Characteristics

1. Excellent rust preventive property in spite of low viscosity.
2. Environmental friendly - Barium-free.
3. Improve work environment - Odorless.
4. Excellent anti-staining property.
5. Easy to degrease with hydrocarbon solvent or alkaline cleaners.
6. Economy due to low oil consumption.
7. Good water displacement properties.

Rust Characteristics

Humidity Cabinet Test	480hrs	A Class
Salt Spray Test	24hrs	A Class
Indoor Exposure Test	720hrs	A Class

Packing

20L pail, 200L drum

The information provided is to our best knowledge, true & accurate, subjected to change without notification due to continual product research and development. All recommendations or suggestions are without guarantee since the conditions of use are beyond our control. The manufacturers do not accept liability for any loss or damage, however arising, which results directly from the use of such information, nor do we offer any warranty of immunity against patent infringement.

Idemitsu Lube India Pvt. Ltd.

603, 6th Floor, Eros Corporate Tower, Nehru Place, New Delhi - 110019, Tel: +91-11-30823600
E-mail: consumercareindia@idemitsu.com | Website: <https://india.idemitsu.com>

PRODUCT DATA SHEET

DAAPHNE SUPER COAT TW High Performance Anti Rust Oil

CHEMICAL AND PHYSICAL PROPERTIES	TEST METHOD	TYPICAL DATA
Specific Density 15 °C g/cm ³	ASTM D-4052	0.8273
Flash Point (COC)°C	ASTM D-92	98
Viscosity, cSt @ 40 °C	ASTM D-445	4.546
Pour Point °C	ASTM D-6749	>-40.0
Total Acid Value (mgKOH/g)	ASTM D-974	2.08
Total Base Number (mgKOH/g)	ASTM D-2896	0.43

The information provided is to our best knowledge, true & accurate, subjected to change without notification due to continual product research and development. All recommendations or suggestions are without guarantee since the conditions of use are beyond our control. The manufacturers do not accept liability for any loss or damage, however arising, which results directly from the use of such information, nor do we offer any warranty of immunity against patent infringement.

Idemitsu Lube India Pvt. Ltd.

603, 6th Floor, Eros Corporate Tower, Nehru Place, New Delhi - 110019, Tel: +91-11-30823600
E-mail: consumercareindia@idemitsu.com | Website: <https://ilindia.idemitsu.com>